

# Walraven WDI2R Drop-in Anchor

(L 03 21)

verkort inslaganker met kraag



## Voordelen en kenmerken

- increased productivity – the reduced 25mm anchor length minimizes drilling depth and speeds up installation
- approved applications in precast prestressed hollow core slabs
- materiaal: staal
- elektrolytisch verzinkt
- brandwerendheidsklasse R30-R120 voor ontwerp van verankeringen onder blootstelling aan vuur
- European Technical Assessment according to EAD 330747-00-0601 (May 2018) for fasteners for use in concrete for redundant non-structural systems
- complies with VdS CEA 4001: 2024-01 (08) for applications with sprinkler systems in concrete elements
- Type ondergrond:
  - gescheurd beton
  - ongescheurd beton
- for loads and more information, refer to the product data sheet and/or the ETA report



Art.nr.	Afmeting	L	d <sub>0</sub> (mm)	h <sub>0</sub> (mm)	h <sub>min</sub> (mm)	h <sub>nom</sub> (mm)	T <sub>(inst.)</sub> (Nm)	VPE 1
6103310825	M8	25 mm	10	≥ 28	80	≥ 25	11,0	100
6103311025	M10	25 mm	12	≥ 28	80	≥ 25	17,0	50
6103311225	M12	25 mm	15	≥ 29	80	≥ 25	38,0	50

