

BIS Obejmy połówkowe (oc. ogniowy) DIN 3567

(B 15 15)

27 - 324 mm



Zalety i właściwości

- obejmą składającą się z dwóch jednakowych części
- ocynkowane ogniowo
- materiał: stal odpuszczana po hartowaniu

Nr kat.	D (mm)	B (mm)	s (mm)	d1 (mm)	k (mm)	k1 (mm)	Pud.
4621027	27	30	5,0	11,5	66	7	-
4621030	30	30	5,0	11,5	68	7	-
4621034	34	30	5,0	11,5	72	7	20
4621038	38	30	5,0	11,5	76	7	-
4621043	43	30	5,0	11,5	82	7	-
4621045	45	30	5,0	11,5	84	7	-
4621049	49	30	5,0	11,5	88	7	-
4621057	57	40	6,0	14,0	104	9	10
4621061	61	40	6,0	14,0	108	9	-
4621077	77	40	6,0	14,0	122	9	-
4621089	89	40	6,0	14,0	136	9	-
4621108	108	50	8,0	18,0	172	11	-
4621115	115	50	8,0	18,0	178	11	-
4621133	133	50	8,0	18,0	196	11	-
4621140	140	50	8,0	18,0	204	11	-
4621159	159	50	8,0	18,0	222	11	-
4621169	169	50	8,0	18,0	232	11	-
4621220	220	50	8,0	18,0	284	11	5
4621273	273	60	8,0	23,0	348	14	-
4621324	324	60	8,0	23,0	398	14	-

