

# BIS Obejmy połówkowe (czarne) DIN 3567

(B 15 10)

20 - 324 mm



## Zalety i właściwości

- obejma składająca się z dwóch jednakowych części
- pokrycie powierzchni: stal czarna
- materiał: stal odpuszczana po hartowaniu

Nr kat.	D (mm)	B (mm)	s (mm)	d1 (mm)	k (mm)	k1 (mm)	Pud.
4620020	20	30	5,0	11,5	57	7	50
4620022	22	30	5,0	11,5	59	7	50
4620025	25	30	5,0	11,5	62	7	50
4620027	27	30	5,0	11,5	66	7	50
4620030	30	30	5,0	11,5	68	7	50
4620034	34	30	5,0	11,5	72	7	50
4620038	38	30	5,0	11,5	76	7	50
4620043	43	30	5,0	11,5	82	7	50
4620045	45	30	5,0	11,5	84	7	50
4620049	49	30	5,0	11,5	88	7	50
4620057	57	40	6,0	14,0	104	9	25
4620061	61	40	6,0	14,0	108	9	25
4620077	77	40	6,0	14,0	122	9	25
4620089	89	40	6,0	14,0	136	9	25
4620108	108	50	8,0	18,0	172	11	25
4620115	115	50	8,0	18,0	178	11	25
4620133	133	50	8,0	18,0	196	11	10
4620140	140	50	8,0	18,0	204	11	10
4620159	159	50	8,0	18,0	222	11	10
4620169	169	50	8,0	18,0	232	11	10
4620194	194	50	8,0	18,0	258	11	5
4620216	216	50	8,0	18,0	280	11	10
4620220	220	50	8,0	18,0	284	11	10
4620267	267	60	8,0	23,0	342	14	-
4620273	273	60	8,0	23,0	348	14	-
4620318	318	60	8,0	23,0	392	14	-
4620324	324	60	8,0	23,0	398	14	-

