

# Walraven Suport Strut

(H 12 50)

fixare pe perete




6658 3 801



6658 3 802

## Caracteristici și beneficii

- instalare rapidă
- ideal for fastening RapidStrut® Fixing Rails as traverses in shafts or racks
- suitable for rails type 21, 41 or 21 Double
- with pre-assembled screws M10x16mm / SW17 and washers 10,5x40mm
- galvanizat electrolic
- material: oțel 1.0332



Art.Nr.	Model	L	B	H	s	s1	d1	k	T <sub>(inst.)</sub>	F <sub>a,y</sub>	F <sub>a,y2</sub>	F <sub>a,x</sub>	F <sub>a,x 2</sub>	Amb. 1
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)	(N)	(N)	(N)	(N)	
66583801	Orizontal	104 mm	40	120	5,0	4,0	19 x 13	80	15,0	4.280*	9.880*	1.760*	1.980*	25
66583802	Vertical	104 mm	40	120	5,0	4,0	19 x 13	80	15,0	4.280*	9.880*	1.760*	1.980*	25

\*F<sub>a,y</sub> and F<sub>a,x</sub> fixed on rail type L (1,5mm thickness) with M12 and 25Nm.  
 \*\*F<sub>a,y2</sub> and F<sub>a,x2</sub> fixed on rail type H (2,5mm thickness) with M12 and 35Nm.

