

BIS Mengering® Sealing Ring

för rör DN 50 - DN 200

(N 20 05)



Funktioner och Fördelar

- enkel att installera (utan glidmedel)
- testad enligt DIN 4060
- för användning upp till 0,5 bar invändigt tryck
- för anslutning och tätning av gjutjärnrör med sockel med SML eller HT / PE-rör
- material: EPDM gummi, svart

Art.nr.	DN	Modell	Typ	fp
7300050	50	GA-collar to SML or GA-Pipe	I	100
7300070	70	GA-collar to SML or GA-Pipe	I	100
7300100	100	GA-collar to SML or GA-Pipe	I	250
7300125	125	GA-collar to SML or GA-Pipe	I	20
7300150	150	GA-collar to SML or GA-Pipe	I	20
7300200	200	GA-collar to SML or GA-Pipe	I	10
7301050	50	GA-collar to SML or GA-Pipe	A	100
7301070	70	GA-collar to SML or GA-Pipe	A	100
7301100	100	GA-collar to SML or GA-Pipe	A	250
7301125	125	GA-collar to SML or GA-Pipe	A	20
7301150	150	GA-collar to SML or GA-Pipe	A	20
7301200	200	GA-collar to SML or GA-Pipe	A	10
7302050	50	GA-collar to HT/PE-Pipe	IS	100
7302125	125	GA-collar to HT/PE-Pipe	IS	20
7303050	50	GA-collar to HT/PE-Pipe	AS	100
7303070	70	GA-collar to HT/PE-Pipe	AS	100
7303125	125	GA-collar to HT/PE-Pipe	AS	20

Sealing Rings for HT-tube (Part No. 730XXXX) DN 40 up to DN 200 on stock.