

SAFETY DATA SHEET WIS Chemical Anchor WVSF 200T Part A

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name WIS Chemical Anchor WVSF 200T Part A

Synonyms; trade names 6099127 WIS Chemical Anchor WVSF 200T

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive. Paste

1.3. Details of the supplier of the safety data sheet

Supplier J. van Walraven Holding B.V.

Industrieweg 5 3641 RK Mijdrecht The Netherlands Tel. 0031 297 23 30 00 Fax. 0031 297 23 30 33 Info.nl@walraven.com

www.walraven.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1295 753400 (Monday to Thursday 08:30 - 17:00; Friday 08:30 - 16:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram





Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

WIS Chemical Anchor WVSF 200T Part A

Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P501 Dispose of contents/ container in accordance with national regulations.

Contains 2-HYDROXYPROPYL METHACRYLATE

Supplementary precautionary

statements

P233 Keep container tightly closed. P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2-HYDROXYPROPYL METHACRYLATE

5-10%

CAS number: 27813-02-1 EC number: 248-666-3 REACH registration number: 01-

2119490226-37

Classification

Eye Irrit. 2 - H319 Skin Sens. 1 - H317

VINYL TOLUENE 5-10%

CAS number: 25013-15-4 EC number: 246-562-2 REACH registration number: 01-

2119622074-50

Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

TITANIUM DIOXIDE >0.5 <1.0%

CAS number: 13463-67-7 EC number: 236-675-5 REACH registration number: 01-

2119489379-17

Classification

Not Classified

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

WIS Chemical Anchor WVSF 200T Part A

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation May cause respiratory irritation.

Ingestion May cause discomfort if swallowed.

Skin contact May cause skin irritation/eczema.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion

products

Oxides of carbon.

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautionsWear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Collect and place in suitable waste disposal containers and seal securely. For waste disposal,

see Section 13.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste

disposal, see Section 13.

SECTION 7: Handling and storage

WIS Chemical Anchor WVSF 200T Part A

7.1. Precautions for safe handling

Usage precautionsDo not use in confined spaces without adequate ventilation and/or respirator.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away

from oxidising materials, heat and flames.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

WEL = Workplace Exposure Limit

2-HYDROXYPROPYL METHACRYLATE (CAS: 27813-02-1)

DNEL Workers - Dermal; Long term systemic effects: 4.2 mg/kg

Workers - Inhalation; Long term systemic effects: 14.7 mg/m³

PNEC Fresh water; 0.904 mg/l

marine water; 0.904 mg/l

STP; 20 mg/l

Sediment (Freshwater); 6.28 mg/kg Sediment (Marinewater); 6.28 mg/kg

Soil; 0.727 mg/kg

VINYL TOLUENE (CAS: 25013-15-4)

DNEL Industry - Inhalation; Long term systemic effects: 37 mg/m³

Industry - Inhalation; Long term local effects: 37 mg/m³

REACH dossier information

PNEC - Fresh water; 0.0498 mg/l

- marine water; 0.002 mg/l - Intermittent release; 0.013 mg/l

- STP; 1 mg/l

Sediment (Freshwater); 0.684 mg/kgSediment (Marinewater); 0.0684 mg/kg

- Soil; 0.133 mg/kg

REACH dossier information

TITANIUM DIOXIDE (CAS: 13463-67-7)

DNEL Industry - Inhalation; Long term systemic effects: 10 mg/m³

REACH dossier information

WIS Chemical Anchor WVSF 200T Part A

PNEC - Fresh water; 0.127 mg/l

- marine water; 1.0 mg/l

- Intermittent release; 0.61 mg/l

- STP; 100 mg/l

- Sediment (Freshwater); 1000 mg/kg - Sediment (Marinewater); 100 mg/kg

- Soil; 100 mg/kg

REACH dossier information

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational

exposure limits for the product or ingredients.

Eye/face protection The following protection should be worn: Chemical splash goggles.

Hand protection It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating,

> smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of

skin. When using do not eat, drink or smoke.

Respiratory protection No specific recommendations.

Environmental exposure

controls

pН

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid Colour Beige.

Odour Aromatic.

Odour threshold Not determined.

Melting point Not determined.

Initial boiling point and range >165°C @

Flash point 53°C

Not determined. **Evaporation rate**

Evaporation factor Not determined.

Not determined. Flammability (solid, gas)

Upper/lower flammability or

explosive limits

Not determined.

Not applicable.

WIS Chemical Anchor WVSF 200T Part A

Other flammability Not determined.

Vapour pressure 6 hPa @ 20°C

Vapour density Not determined.

Relative density 1.65 - 1.75 @ 20°C

Bulk density Not applicable.

Solubility(ies) Insoluble in water

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity > 60 S ISO2431

Explosive properties No information available.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Organic peroxides/hydroperoxides.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Does not decompose when used and stored as recommended.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Organic peroxides/hydroperoxides.

10.6. Hazardous decomposition products

Hazardous decomposition

Oxides of carbon.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 159.89

Skin sensitisation

Skin sensitisation Sensitising.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Coughing.

Ingestion May cause discomfort if swallowed.

WIS Chemical Anchor WVSF 200T Part A

Skin contact May cause sensitisation by skin contact. May cause irritation.

Eye contact Irritating to eyes.

Acute and chronic health

hazards

Irritating to eyes. May cause sensitisation by skin contact.

Route of exposure Skin and/or eye contact.

Medical symptoms Irritation of eyes and mucous membranes. Skin irritation.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

2-HYDROXYPROPYL METHACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD50

11,200.0

mg/kg)

Species Rat

ATE oral (mg/kg) 11,200.0

VINYL TOLUENE

Acute toxicity - oral

Acute toxicity oral (LD50

2,255.0

mg/kg)

Species Rat

ATE oral (mg/kg) 2,255.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 4,500.0

mg/kg)

Species Rat

ATE dermal (mg/kg) 4,500.0

Acute toxicity - inhalation

ATE inhalation (vapours

mg/l)

11.0

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

VINYL TOLUENE

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: 23.4 mg/l, Pimephales promelas (Fat-head Minnow)

WIS Chemical Anchor WVSF 200T Part A

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 1.3 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: 2.6 mg/l, Selenastrum capricornutum

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

2-HYDROXYPROPYL METHACRYLATE

Partition coefficient log Kow: 0.93

VINYL TOLUENE

Partition coefficient log Pow: 3.36

12.4. Mobility in soil

Mobility Not applicable.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Dispose of waste via a licensed waste disposal contractor.

Waste class

The waste code classification is to be carried out according to the European Waste Catalogue

(EWC).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1866 UN No. (IMDG) 1866 UN No. (ICAO) 1866 UN No. (ADN) 1866

14.2. UN proper shipping name

Proper shipping name

RESIN SOLUTION

(ADR/RID)

Proper shipping name (IMDG) RESIN SOLUTION

Proper shipping name (ICAO) RESIN SOLUTION

WIS Chemical Anchor WVSF 200T Part A

Proper shipping name (ADN) RESIN SOLUTION

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number 30

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation (EU) No 2015/830

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

WIS Chemical Anchor WVSF 200T Part A

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 08/05/2018

Version number 2.000

Supersedes date 14/04/2016

SDS number 20907

Hazard statements in full H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.