

Smart and durable
pipe fixing



starQuick®

For Mechanical, Electrical & Plumbing Installations



starQuick®




For indoor & outdoor use



One-part clamp



Clamp closes by applying pressure to the pipe



starQuick® – the UV resistant and halogen free pipe clamp with a difference!

This range of versatile pipe clamps can be used to quickly and securely install multiple pipe runs for heating, plumbing and electrical installations all over the world. The smart self-closing feature means the clamp closes securely when the pipe is simply pushed into it. Press down again to easily unlock if required.

Suitable for copper pipe and steel conduit, as well as for electrical plastic rigid and flexible tubes, in the range of Ø 10-65mm.

This pipe clamp comes with a full range of accessories to enable easy fixing to any substrate, to rail or strut and to threaded rod. A truly versatile solution!

Loved by installers on Instagram

@pbplumber Peter Booth is a fan of the starQuick® clamp. He recently posted about it on his Instagram page.

Peter told us: "I couldn't believe I hadn't seen these clamps before, and that one clamp had so many features. I really like the two-step closing, so you can still move the pipe before the second click fixes it in place. And they unlock really easily too, without damaging them. I've just replaced all the clamps in my van with these."

Photo: Copper colour starQuick® installed vertically on the wall and horizontally under the floor mounted on our extendable RSWB.

starQuick®

Features and benefits

Wide range

- From 10-65 mm diameter
- Special design also available for pipes 71 – 115 mm diameter

Material and finish

- The clamp is made of Polyamide (PA6) which is durable, strong and impact resistant
- Available in grey, white or copper colour
- Clamp design is aesthetically pleasing

Sustainable

- The starQuick® is UV stable so it will not degrade in sunlight like polypropylene clamps
- It is also recyclable and halogen free

Suitable for specialist environments

- The properties of Polyamide make this clamp suitable for a range of specialist environments such as swimming pools, chemical factories, zinc factories, and outdoor use.

Temperature resistance

- The starQuick® clamps are temperature resistant from -40°C to +90°C (constant) or +130°C (intermittent)

Special installation features

- Easy, self-closing – simply push the pipe into the clamp
- Press down again to easily unlock
- Ridges allow multiple clamps to be attached together for close running pipes
- Range of accessories allow easy fixing direct to walls, ceilings, rail, strut, threaded rod and more!
- Aesthetically pleasing design, perfect for exposed installations

Can be used with the RSWB

To easily fix pipes between floor joists or in stud walls, the starQuick® can be attached to our RSWB (Rapid Sliding Wall Bracket).



Request a sample

We have sample packs available which include both the starQuick® pipe clamps and the full range of accessories. To really appreciate the value of this fixing system you should try it yourself!

Send an e-mail to export@walraven.com to request your free sample.



starQuick®

Installation guide


Fixing of two or more pipes



1. Tacking ≤ SQ-28



2. Duo-Wall Plate ≤ SQ-20




3. Fixing Rail ≤ SQ-32

Fixing to wall or floor




Fixing to threaded rod



≤ SQ-51

Fixing with a distance



≤ SQ-36

Fixing to metal rail



For BIS RapidRail®



Universal Rail Adaptor for BIS RapidRail® and BIS RapidStrut® ≤ SQ-51

*A truly smart
fixing solution!*

starQuick®

Clamps



Grey

Part No.	Part No. (M6 nut)	Type	D (mm)	D (")	D (DN)	Fa,z (N)	Fb,z (N)	Box qty (pc)	Outer box qty (pc)
0854010	-	SQ-10	10 - 12	1/8	6	170	500	100	1200
0854012	0854612	SQ-12	12 - 14	1/4	8	180	550	100	1200
0854015	0854615	SQ-15	14 - 16	-	-	200	600	100	1200
0854018	0854618	SQ-17	16 - 20	3/8	10	230	700	100	800
0854022	0854622	SQ-20	20 - 23	1/2	15	270	800	50	600
0854028	0854628	SQ-25	24 - 28	3/4	20	280	850	50	600
0854031	0854631	SQ-28	28 - 32	-	-	300	900	50	400
0854035	0854635	SQ-32	32 - 35	1	25	330	1000	50	400
0854038	0854638	SQ-36	35 - 40	-	-	370	1100	25	300
0854042	0854642	SQ-40	40 - 44	1 1/4	32	400	1200	25	200
0854050	0854650	SQ-47	44 - 50	-	-	430	1300	25	200
0854054	0854654	SQ-51	48 - 55	1 1/2	40	470	1400	15	180
0854063	-	SQ-59	59 - 65	2	50	500	1500	15	180



White

Part No.	Type	D (mm)	D (")	D (DN)	Fa,z (N)	Fb,z (N)	Box qty (pc)	Outer box qty (pc)
0855010	SQ-10	10 - 12	1/8	6	170	500	100	1200
0855012	SQ-12	12 - 14	1/4	8	180	550	100	1200
0855015	SQ-15	14 - 16	-	-	200	600	100	1200
0855018	SQ-17	16 - 20	3/8	10	230	700	100	800
0855022	SQ-20	20 - 23	1/2	15	270	800	50	600
0855028	SQ-25	24 - 28	3/4	20	280	850	50	600
0855031	SQ-28	28 - 32	-	-	300	900	50	400
0855035	SQ-32	32 - 35	1	25	330	1000	50	400
0855038	SQ-36	35 - 40	-	-	370	1100	25	300
0855042	SQ-40	40 - 44	1 1/4	32	400	1200	25	200
0855050	SQ-47	44 - 50	-	-	430	1300	25	200
0855054	SQ-51	48 - 55	1 1/2	40	470	1400	15	180
0855063	SQ-59	59 - 65	2	50	500	1500	15	180



Copper

Part No.	Type	D (mm)	D (")	D (DN)	Fa,z (N)	Fb,z (N)	Box qty (pc)	Outer box qty (pc)
0855812	SQ-12	12 - 14	1/4	8	180	550	100	1200
0855815	SQ-15	14 - 16	-	-	200	600	100	1200
0855818	SQ-17	16 - 20	3/8	10	230	700	100	800
0855822	SQ-20	20 - 23	1/2	15	270	800	50	600
0855828	SQ-25	24 - 28	3/4	20	280	850	50	600
0855831	SQ-28	28 - 32	-	-	300	900	50	400



3KUP
Pipe clamps
(0854010 - 0854063)
(0854612 - 0854654)

kiwa

(0854012 - 0854042)
(0855012 - 0855042)
(0855812 - 0855831)







Fa = maximum allowed load. Fb = breaking load.

starQuick®

Accessories

	Part No.	Description	Dimension	Box qty (pc)	Outer box qty (pc)
A	0854000	Duo-Wall Plate (grey)	50 mm	100	1200
	0855000	Duo-Wall Plate (white)	50 mm	100	1200
B	0854356	Threaded Rod Adaptor	M6	100	1200
	0854358	Threaded Rod Adaptor	M8	100	1200
C	0854510	Distance Block	10 mm	25	250
D	0854301	Hammer-in Screw	Ø 6 x 40 mm	25	250
E	0854325	Rail	1 m	25	-
F	0854313	Rail Adaptor	starQuick® Rail	20	200
G	0854006	Fixing Nut (grey)	M6	100	1000
	0855006	Fixing Nut (white)	M6	100	1000
	0854308	Fixing Nut (grey)	M8	100	1000
H	6101063	Push Plug	M6	50	500
I	0854338	Hammerfix M8	WMO, 1, 15, 2, 30, 35	50	600
J	0854332	Universal Rail Adaptor	WMO, 1, 15, 2, 30, 35 + Strut	50	600



Find out how we can support you

Would you like to find out more about any of the solutions described in this brochure?
Or would you like to discuss how we could help you find the best possible solution for your project? Get in touch today!

Other countries

Walraven International

Industrieweg 5
3641 RK Mijdrecht (NL)
Tel. +31 297 23 30 00
Fax +31 297 23 30 99
export@walraven.com

Walraven Group

Mijdrecht (NL) · Tienen (BE) · Bayreuth (DE) · Banbury (GB) · Malmö (SE) · Grenoble (FR) · Barcelona (ES) · Kraków (PL)
Mladá Boleslav (CZ) · Moscow (RU) · Kyiv (UA) · Detroit (US) · Shanghai (CN) · Dubai (AE) · Budapest (HU) · Mumbai (IN)
Singapore (SG)

